

The CT-1000HT series constant temperature bath accommodates viscometer tubes requiring a bath depth up to 12" and provides reliable temperature control from 25 °C to 200 °C. The unit accommodates up to 7 simultaneous viscosity determinations.

Common Applications

- Formulated oil analysis
- Hydraulic oil analysis
- Additive analysis
- Marine fuel testing
- Base stock analysis
- Light and heavy fuel testing
- Waxes/paraffin
- Crude oil testing
- Glycols

CT-1000 HT

Extended Range Constant Temperature Bath

For Kinematic Viscosity from 25 °C to 200 °C
ASTM D445/D446, ISO 3104/3105

Product Features & Benefits

Precise & accurate temperature control

- Temperature range: 25 °C to 200 °C*
- Temperature accuracy: ± 0.01 °C from 25 °C to 100 °C; ± 0.03 °C from 100 °C to 200 °C
- Temperature selection is variable between 25 °C and 200 °C or selectable at ten pre-set temperatures [25 °C, 40 °C, 60 °C, 80 °C, 100 °C, 135 °C, 150 °C, 165 °C, 185 °C and 200 °C]
- Meets ASTM D445 temperature sensitivity requirements for kinematic viscosity determination
- Motor driven stirrer ensures a uniform bath temperature

Safe operation

- Bath thermistor senses over-temperature fault and removes power
- Thermistor disconnection results in removal of bath heater power
- Liquid level sensor prevents operation if bath liquid is not at a safe operating level

Efficient, user-friendly design

- Seven glass viscometer ports (each 2" in diameter) and two thermometer ports (each 0.4" in diameter) allow up to 7 simultaneous viscosity determinations
- Two electric heating elements quickly heat bath media to the selected temperature
- Stainless steel baffle provides a plain reflective viewing background
- Integrated stainless steel cooling coil allows connection to tap or recirculating water chiller for temperatures slightly above or below ambient. An external thermoelectric bath cooler is also available.
- Convenient drawer provides easy access to electrical controls

Reliable performance

- Well tested CANNON bath platform offers reliability and dependable support
- All wetted components are manufactured from high quality stainless steel or glass
- The heavy duty aluminum frame offers a corrosion-resistant epoxy finish

*Test temperatures <40 °C and high ambient temperature test environments require an optional bath cooler

**Other port configurations are available as a special order



2139 High Tech Road | State College | PA | 16803
800-676-6232 | 814-353-8000 | Fax 814-353-8007

sales@cannoninstrument.com | www.cannoninstrument.com

CT-1000HT Extended Range Constant Temperature Bath

Ordering Information

CT-1000HT Extended Range Constant Temperature Bath consists of the bath unit and viscometer port covers. Vicometer tubes, holders, bath oil and thermometer sold separately.

Description	Part #
120 VAC, 50/60 Hz	9726-A27
240 VAC, 50/60 Hz	9726-A29

Options

NOTE: Part numbers are listed below for field installable options.

Description	Part #
Thermoelectric Bath Cooler [external]	
CBC-100 with U.S. plug	9726-D05
CBC-100 with non-U.S. plug	9726-D10

Accessories & Consumables

Description	Part #
Glass viscometers & holders	various
Storage drawer	9726-A50
Port cover set [7 covers; 2 thermometer holders]	22.39
Bath oils	
IBF oxidation resistant bath oil [22.7 L/6 gal]	9726-L20
Silicone bath oil, 10 cSt [18.9 L, 5 gal]	9726-L30
Silicone bath oil, 20 cSt [18.9 L, 5 gal]	9726-L33
Silicone bath oil, 50 cSt [18.9 L, 5 gal]	9726-L36
Silicone bath oil, 10 cSt [3.8 L, 1 gal]	9726-L37
Silicone bath oil, 20 cSt [3.8 L, 1 gal]	9726-L38
Silicone bath oil, 50 cSt [3.8 L, 1 gal]	9726-L39
Dostmann digital thermometer	61.5600
Standard thermometer probe	61.5601
CANNON pressure/vacuum pump	9726-L96
3VM vacuum manifold, 3 valves	9726-V10
4VM vacuum manifold, 4 valves	9726-V05
Neoprene vacuum tubing, 10 ft [1/4 in bore x 5/8 in OD]	9726-V23
DVR-1000 [requires vacuum source]	
Available in vertical/horizontal and 120 VAC/240 VAC configurations	See flyer
DVR-1500 [with built-in vacuum pump]	
Available in vertical/horizontal and 120 VAC/240 VAC configurations	See flyer

Product Specifications

Dimensions [W x D x H]	43.8 cm x 46.4 cm x 58.4 cm [17.25 in x 18.25 in x 23 in]
Weight	43 kg [95 lb]
Shipping dimensions [W x D x H]	61 cm x 50.8 cm x 109.2 cm [24 in x 20 in x 43 in]
Shipping weight [with all items]	56.7 kg [125 lb]
Temperature range & accuracy	25 °C to 100 °C ± 0.01 °C* 100°C to 200 °C ± 0.03 °C *Test temperatures <40 °C and high ambient temperature test environments require an optional bath cooler
Sample capacity	7
Bath height	12 in
Bath volume	17 L [4.5 gal]
Operating conditions	15 °C to 30 °C, 10% to 75% relative humidity (non-condensing), Installation Category II; Pollution Degree 2
Electrical specifications	120 VAC, 50/60 Hz; 240 VAC, 50/60 Hz; 1,400 watts power consumption
Compliance	CE Mark; EMC directive [2004/108/EC]; Low voltage directive [2006/95/EC]; HI-POT [1900 VDC, 60 sec.]; ROHS

CANNON Instrument Company® provides a variety of physical property testing equipment and consumables [vials, bath fluids, and reference materials] for your testing needs. To learn more, contact sales@cannoninstrument.com.



2139 High Tech Road | State College | PA | 16803
800-676-6232 | 814-353-8000 | Fax 814-353-8007

email: sales@cannoninstrument.com | www.cannoninstrument.com